

PRODUCT DATA SHEET

WEATHERGARD HI-GLO

Description	<p>WEATHERGARD HI-GLO is a high-quality acrylic water-based paint, delivering a gloss finish and a sophisticated appearance for any structure. The product is formulated to provide dependable protection for exterior walls.</p> <p>With good resistance to weathering and alkali, the coating effectively withstands harsh outdoor conditions, while its anti-algae and fungus properties help maintain a clean and beautiful finish over time.</p>
Type	Acrylic Polymer Coating
Uses	<p>A good performance coating for the protection of exterior surfaces such as:</p> <p>- Cement plasters - Concrete - Brickworks...</p>
Finish	<p>Hiigh Gloss</p> <p>Colour: Wide range of decorative colours as per colour card. Special colours on request.</p>
Features	<ul style="list-style-type: none"> - 6 years protection - Good resistance to weathering - Good alkaline resistance - Smooth surface with a gloss finish - Anti-algae and fungus - Non-toxic, does not contain Lead, Mercury and heavy metals - Low VOCs (containing < 50g/L VOC, meeting the VOC requirement)
APPLICATION DATA	
Surface Preparation	<p>Surface must be clean, dry, and stable.</p> <p><u>Suggested Treatment:</u></p> <p><u>Dirt/Powder:</u> High pressure water wash. Mild detergent may be used. For very powdery surface, apply a coat of HITEX 5180 SEALER after cleaning.</p> <p><u>Old Paint/Plaster/Skimcoat:</u> Unstable old film / substrate should be removed by chisel, scraper, powder grinder whichever is appropriate. Uneven substrates must be re-plastered with an approved putty / skimcoat.</p> <p><u>Moisture:</u> High moisture will cause paint defect. Observe the following level prior to painting:</p> <ul style="list-style-type: none"> - Masonry: below 16% by Protimeter Mini BLD 2000 Moisture meter <li style="padding-left: 40px;">below 60% by Lutron MS-7003 Moisture meter <p>All water seepage must be checked and repaired.</p> <p><u>Algae/Fungus:</u> Remove by high pressure wash or by chisel, scraper and treat with</p>

